

H2O THREAD LUBE

NEVER HAVE A SEIZED NUT AGAIN

- STOPS CORROSION
- STOPS THREAD GALLING
- PROTECTS FROM CORROSION
- PREVENTS SEIZED PARTS
- LUBRICATES BEARINGS



H2O Thread Lube

A revolutionary new product that prevents galling and rusting of nuts and bolts that causes them to seize together. Use **H2O Thread Lube** any where you need lubrication and rust protection.

- Ion-blocking technology stops corrosion
- High pressure and high temperature
- Resists melting at high temperatures
- Does not freeze at low temperatures
- Meets ASTM D 3428, NLG1 and GC-LB

Applications include nuts and bolts, pipe connections, gear surfaces, ball joints, wheel-bearings and NEMA class A electric motors. **H2O Thread Lube** is an excellent automotive and industrial lubricant.

H2O Thread Lube is available in brush top cans.

COMPOUND		HYDROCARBON BASE
COLOR		RED TO LIGHT BROWN
BASE VELOCITY @ 40°C		CST 146
DROP POINT	ASTM D2250	260 - 500°C
OIL SEPARATION	ASTM D1742	0.7
WHEEL BEARING	ASTM D1263	0.3
TIMKEN LOAD	ASTM D2509	60
WATER WASH	ASTM D1254	4
CORROSION	ASTM D1743	PASS

H2O CONTROL PRODUCT

Phone: 705-522-5300

Fax: 705-523-0761

www.h2ocontrolproducts.com