

MATERIAL SAFETY DATA SHEET

SECTION I - CHEMICAL PRODUCT AND COMPANY INFORMATION

H2O Control Products Inc.
633 Lorne Street, Sudbury, ON P3C 4R3
Tel: (705) 522-5300 Fax: (705) 523-0761
PRODUCT TRADE NAME: THREAD LUBE
CAS NO: Not Applicable for Mixtures.
GENERIC/CHEMICAL NAME: Petroleum Lubricating Grease
PRODUCT TYPE: Thread Lubricant
PREPARATION/REVISION DATE: Jan 8, 2010

SECTION 2 - COMPOSITION INFORMATION

Distillates (petroleum), hydro treated 64742-52-5 >94%
Heavy naphthenic and Residual oils (petroleum), solvent dewaxed 64742-62-7
Lithium complex soap thickener Proprietary additives <6%
All components of this product are listed on the US TSCA inventory.

SECTION 3 - HAZARDS IDENTIFICATION

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks, which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized. Prolonged or repeated skin contact may cause skin irritation.

SECTION 4 - FIRST AID MEASURES

Eye contact: Flush with enough water to wash away any irritant. If irritation persists, seek professional help.
Skin: In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse.
Inhalation: Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem.
Ingestion: If ingested, DO NOT induce vomiting, seek professional help.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: (minimum) 221 C (430F) COC method
Auto ignition Temp. >260 C (500F)
Use product with caution around heat, sparks, pilot lights, static electricity, and open flame.
Flammable or Explosive limits (Approx. percent by volume of air):
Estimated values: Lower flammable limit 0.9% Upper flammable limit 7%
Extinguishing media and fire fighting procedures: Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size and potential size of fire and circumstances related to the situation. Use water spray, dry chemical, foam or carbon dioxide to extinguish the fire. Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapor and to provide protection for persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplies-air breathing equipment for enclosed or confined spaces or as otherwise needed.
Decomposition Products: Fumes, smoke, carbon monoxide, sulfur oxides, phosphorus oxides, metal oxides, aldehydes, and other decomposition products, in case of incomplete combustion.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: recover free product, Add sand, earth, or other suitable absorbent to spill area, Minimize skin contact. Keep product out of sewers and watercourses by diking or impounding. Assure conformity with applicable governmental regulations.

SECTION 7 - HANDLING AND STORAGE

Keep containers closed when not in use. Wash with soap and water or hand cleaner after handling. Empty containers may retain material residue. Do not expose containers to heat, flame, or other sources of ignition. Do not store near potential sources of heat.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Ventilation: Use local exhaust to capture vapor, mists or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentration on vapors in air, if necessary.

Respiratory Protection: Use supplied-air respiratory protection in confined or enclosed spaced, if needed.

Protective Gloves: Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Eye protection: Use splash goggles or face shield when eye contact may occur.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

The following data is approximate or typical values:

Boiling Range: IBP Approx. 310 C (590 F) by ASTM D 2887

Vapor Pressure: Less than 0.01 mmHG @ 20 C

Specific Gravity 0.93 Vapor Density: (air=1):>5 pH: Essentially neutral Melting Point: 260 C (500 F) by ASTM D2887

Viscosity: 325 worked penetration, mm/10, @ 25 C, ASTM D217

SECTION 10 - STABILITY AND REACTIVITY

This product is stable and will not react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium, hypochlorite, etc., as this presents a serious explosion hazard.

SECTION 11 - DISPOSAL CONSIDERATIONS

Dispose of in an approved landfill. Consult Federal or Provincial authorities for more restrictive requirements.

SECTION 12 - TRANSPORT INFORMATION

US DOT SHIPPING DESCRIPTION: NOT REGULATED.

SECTION 13 - REGULATORY INFORMATION

None Known

The information presented here has been compiled from sources considered to be dependable and is accurate to the best of H2O Control Products Inc's knowledge; however, H2O Control Products Inc. makes no warranty whatsoever, expressed or implied, of merchant ability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons H2O Control Products Inc. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risk. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, H2O Control Products Inc. cannot guarantee that these are the only hazards that exist. It is the sole responsibility of the user to comply with all applicable Federal, Provincial, and Municipal laws and regulations.